

ID551301BZC (2.700 K - IP20)
ID551305BZE (3.000 K - IP20)
ID551302BZD (4.000 K - IP20)

Compatibele profielen



Technische gegevens

Warm wit (2.700 K of 3.000 K) of natuurlijk wit (4.000 K)

7,2 W / m = 36 W / 5 m

180 LEDs / m = 900 LEDs / 5 m

24 V DC voeding **verplicht** (DIM )

Compatibele radiocontroller :

- zender **ID836359BZZ** (LO KINGSTON EM MONO)

- ontvanger **ID836060ZZZ** (LO KINGSTON REC RGB-MONO-TW)

Compatibele profielen : **ALBI, ALMADA, AVEIRO, BARI, BOOM, CALVI, CUBA, CUBA 2.0, DOUR, HUY, LEON, LUGO, MALTA, MERIBEL, PALMA, PORTO, SINES, SPA** of **VIGO**

L70 B30 50.000 uren

> 30.000 ON / OFF

Knipbaar om de 33,33 mm / 6 LEDs

Aansluitkabels links en rechts


Bevestiging met dubbelzijdige kleefband

Maximaal aantal van strips na elkaar: 2 (10 m)

Werkings temperatuur: -20 tot +45 °C

Gloeidraadtest: 650°

Afmetingen (mm)



REFERENTIE(S)	BESCHERMING	KLEUR	LUMEN
ID551301BZC (LO MERIDA 2700K)		2.700 K	580 lm / m
ID551305BZE (LO MERIDA WW)	IP20	3.000 K	600 lm / m
ID551302BZD (LO MERIDA NW)		4.000 K	620 lm / m